

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 28 December 2000 (28.12.2000)

PCT

(10) International Publication Number WO 00/79233 A1

(51) International Patent Classification⁷: G01D 5/26

Martin [SE/SE]; Berglärkan 29, S-426 69 Västra Fröhunda (SE). HÖJER, Svante [SE/SE]; Fredkullagatan 21, S-442 35 Kungälv (SE).

(74) Agents: ANDERSSON, Per et al.; Albihns Patentbyrå Göteborg AB, P.O. Box 142, S-401 22 Göteborg (SE).

- (21) International Application Number: PCT/SE00/01296
- (22) International Filing Date: 16 June 2000 (16.06.2000)
- (25) Filing Language:

Swedish

G01L 11/02.

(26) Publication Language:

English

(30) Priority Data:

9902320-2

18 June 1999 (18.06.1999) SI

- (71) Applicant (for all designated States except US): SAMBA SENSORS AB [SE/SE]; Första Långgatan 26, S-413 28 Göteborg (SE).
- (81) Designated States (national): JP, US.
- (84) Designated States (regional): European patent (AT. BE. CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published:


- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

(72) Inventors; and

(75) Inventors/Applicants (for US only): VIDOVIC, Nevio [SE/SE]; Ekvägen 1, S-428 37 Kållered (SE). KRANTZ,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD AND A DEVICE FOR BENDING COMPENSATION IN INTENSITY-BASED FIBRE-OPTICAL MEASURING SYSTEMS



(57) Abstract: The invention relates to a method for bending compensation in intensity-based optical measuring systems, comprising a sensor element (8) connected to a measuring and control unit (16) via an optical connection (4), and being adapted for providing a signal corresponding to a measurement of a physical parameter in connection with the sensor element (8), said method comprising the generation of a measuring signal (λ₁) that is brought to come in towards the sensor element (8), the generation of a reference signal (λ₂) that is transmitted through the optical connection (4) without being influenced in the sensor element (8), said measuring signal and said reference signal having different wavelengths, the detection of said measuring signal (λ₁) and the detection of said reference signal (λ₂). The invention is characterised by comprising bending compensation through correction data based upon pre-stored data concerning the relationship between the measured reference signal (λ₂) and the measured measuring signal (λ₄) as a function of the bending influence on said optical connection (4). The invention also relates to a device for carrying out said method. Through the invention, measurements with an optical pressure measuring system are allowed, which exhibit effective compensation for any bending of the optical connection.

